

**We stock them,
so you don't have to.**




Different fitting options available.

- Dome Head or Louvre options available
- Installing into concrete, or soft ground? We've got different mounting kits available for different applications

Need them in a hurry?

- Get Next Day Delivery **direct to site** when you order before 6pm - so you don't have to touch the stock!

**TRI-COLOUR
3000K, 4000K OR 6000K**



WEATHERPROOF CONNECTOR



PROTECT YOUR FITTING FROM IMPACT



LED Bollard Key Data

Power	25W
Luminous Flux	2000lm
Colour Temperature	3000K/4000K/6000K
IP Rating	IP65
IK Rating	IK10
Dimensions	Ø160 x 1000mm
Warranty	3 Years



Dome Head
NET-53-14-02



Louvre Reflector
NET-53-14-06



Anchor Mounting Kit
NET-53-14-08



Deep Root Kit with J Bolts
NET-53-14-09

LED Technical Specifications

Colour Rendering	>80 CRI
Driver Output Voltage (DC)	28-38V
Input Voltage (AC)	220-240V
Lamp Viewing Angle	180°
LED Manufacturer	Duris
LED Type	SMD 2835
Luminaire Efficacy	90-100lm/W
Operating Temperature	-25°C to +40°C
Photocell Compatible	No
Power Factor	>0.9
Total Circuit Power (W)	22W
Weight	5.5Kg
Driver Manufacturer	BOKE
Electrical Class	1
Housing Colour	Black
Housing Material	Aluminium
Lifespan LM80	50,000 Hours
Diffuser Material	Acrylic
Dimmable	No
Manufacturer	Kingsway Lighting Ltd.