

# Say goodbye to glare.



## Ideal for commercial offices with a UGR<19 rated diffuser

- The low glare diffuser reduces glare, creating a softer light and more comfortable environment - particularly helpful in spaces where people spend extended periods such as offices, classrooms or healthcare facilities.

## Available in Emergency, Dimmable and DALI Emergency

- Prioritise safety with the integrated 3H Emergency Kit which provides up to three hours of light in the event of a power failure
- The Tridonic one4all Dimmable driver allows for seamless dimming, giving users precise control over the light output

**LOW GLARE UGR<19  
RATED DIFFUSER**



**STAINLESS STEEL  
SPRING CLIPS**



**OPTIONAL MANUAL/  
SELF TEST EMERGENCY KIT**



# Technical Specifications

Colour Rendering	>80 CRI
Driver Output Voltage (DC)	40V
Input Voltage (AC)	220-240V
Lamp Viewing Angle	60°
Luminaire Efficacy	109lm/W
LED Manufacturer	Tridonic
Operating Temp.	-15°C to +40°C
Power Factor	0.95
UGR Rating	<19
Electrical Class	2
Housing Colour	White
Housing Material	Aluminium
Lifespan LM80	50,000 Hours
Driver Manufacturer	Tridonic
Dimmable	Optional
Dimming Input Type	Tridonic one4all Dimming - DALI 1 & 2 and switchDIM (Push)
Manufacturer	Tridonic



**DALI 3W  
Emergency Kit**  
NET-61-33-03



**Manual/Self Test  
Emergency Kit**  
NET-50-12-08

## Part Numbers

Part Number	Description
<b>6" Downlights</b>	
NET-60-05-06	Standard
NET-60-05-07	Emergency
NET-60-05-08	Dimmable one4all
NET-60-05-09	Dimmable Emergency
NET-60-05-10	Dimmable DALI Emergency
<b>8" Downlights</b>	
NET-60-05-26	Standard
NET-60-05-27	Emergency
NET-60-05-28	Dimmable one4all
NET-60-05-29	Dimmable Emergency
NET-60-05-30	Dimmable DALI Emergency

Order now over at  
[www.mynetled.co.uk](http://www.mynetled.co.uk)

 **ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

 **NET LED  
LIGHTING**