

# Selectable in more ways than one.

Ø470mm  
in diameter!

## One of our most flexible fittings

- Optional DALI Addressable Emergency Kit
- DALI 1 & 2 and switchDIM options
- 3H Emergency and Self Test Emergency options
- Selectable power setting 14W or 20W at the time of installation
- Selectable colour temperature 3000K, 4000K or 5500K

## Perfect for school corridors and stairwells

- Reduce energy costs and ensure lighting is only on when required with the 0, 10 or 25% Standby Modes on all Microwave Sensor options
- High output Emergency Kit to guide people safely on stairwells in the event of an emergency

**HINGED GEAR TRAY  
FOR EASY ACCESS**



**EMERGENCY AND SELF TEST  
EMERGENCY OPTIONS AVAILABLE**



**0, 10 OR 25% STANDBY  
MODES ON MICROWAVE OPTIONS**



# Technical Specifications

Colour Rendering	>80 CRI
Driver Output Voltage (DC)	36-42V
Fire Rating	V2
Input Voltage (AC)	220-240V
Lamp Viewing Angle	115°
LED Manufacturer	Jingrui
LED Type	SMD 2835
Luminaire Efficacy	100lm/W
Operating Temp.	-15°C to +45°C
Power Factor	>0.9
UGR Rating	More than 19
Weight	2.01Kg
Driver Manufacturer	Tridonic Advanced Series
Electrical Class	2
Housing Colour	White
Housing Material	Polycarbonate
Lifespan LM <sub>80</sub>	50,000 Hours
Diffuser Material	Polycarbonate
Dimmable	Dimmable Options Available
Manufacturer	NET LED Lighting



**Chrome Ring**  
NET-33-06-02



**Matte Black Ring**  
NET-33-06-04

## Available in



Emergency, Self Test Emergency & DALI Addressable



DALI 1 & 2 and switchDIM



Microwave Sensor

**We stock them, so  
you don't have to!**  
Delivery direct to  
branch or site.

**Order now over at**  
[www.mynetled.co.uk](http://www.mynetled.co.uk)



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

**NET LED**  
LIGHTING