

DUXFORD BULKHEAD MULTI-WATTAGE 4000K IP65 EMERGENCY/SELF TEST

NET-33-06-42







Features & Benefits

- · Manual or self test selectable emergency operation
- Single colour temperature 4000K
- IP65 rated housing
- · Shatterproof all-polycarbonate diffuser
- · Raised mounting plate
- 3 rear entry positions

Key Data

Power 12W/14W/16W/18W

Luminous Flux 1200lm/1400lm/1600lm/1800lm

Colour Temperature 4000K
IP Rating IP65

Dimensions Ø325 x 110mm Warranty 3 Years

Compatible Accessories

Γ	NET-51-04-59	Photocell Kit for Outdoor Lighting

NET LED Lighting

Buckingway Business Park, 300 Anderson Road, Swavesey, Cambridge, CB24 4UQ



Technical Specifications

Input Voltage (AC) 220-240V

Power Factor >0.9

Luminaire Efficacy 100lm/W

LED Manufacturer Jingrui

LED Type SMD 2835

No. of LEDs 52

Driver Manufacturer Tridonic

Driver Output Voltage (DC) 36-42V

Total Circuit Power (W) 12W/14W/16W/18W

Electrical Class 1

Colour Rendering>80 CRILamp Viewing Angle115°DimmableNo

Operating Temp. 0°C to +45°C
Lifespan LM80 35,000 Hours
UGR Rating More than 19
Weight 1.13Kg


Manufacturer NET LED Lighting

Fire Rating V2 Luminous Flux Factor 5%

Self Test Selectable
Housing Colour White

Housing MaterialPolycarbonateBattery PackLi-on 3.7VDiffuser MaterialPolycarbonateEmergency Kit1 Year Warranty

Emergency Operation >3H
Emergency Pack Streamer



Other Options

	Description	
NET-33-06-40	Duxford Bulkhead Multi-Wattage 4000K IP65 Standard	
NET-33-06-42	Duxford Bulkhead Multi-Wattage 4000K IP65 Emergency/Self Test	
NET-33-06-44	Duxford Bulkhead 4000K IP65 16W Microwave Sensor	
NET-33-06-46	Duxford Bulkhead 4000K IP65 16W Microwave Sensor Emergency/Self Test	

NET LED Lighting

Buckingway Business Park, 300 Anderson Road, Swavesey, Cambridge, CB24 4UQ



SHATTERPROOF POLYCARBONATE DIFFUSER

Prevents the fitting from breaking into multiple small pieces

IP65 RATED HOUSING

Protect your bulkhead from water and dust



4K



SELECTABLE COLOUR TEMPERATURE

Choose your colour temperature 3000K, 4000K or 5500K



MULTI WATTAGE DRIVER

Choose between 12W, 14W, 16W or 18W at the time of installation

NOT on Microwave Sensor options

NEW

MANUAL OR SELF TEST EMERGENCY SELECTABLE

Choose between manual emergency or self test emergency at the time of installation

Emergency options only

DUSK TO DAWN FUNCTION

Detects ambient light levels and adjusts the light accordingly

Photocell options only

PUSH CONNECTOR

Reduce installation time with easy-to-use push fit terminals



SUITABLE FOR BESA BOX INSTALLATION

Save time on site with pre-made cable entry points



Featuring a 0 or 10% Standby Mode, 2-10m detection range and 5sec to 10min hold time

Microwave Sensor options only

