

DUXFORD BULKHEAD 4000K IP65 16W MICROWAVE SENSOR EMERGENCY/SELF TEST

NET-33-06-46







Features & Benefits

- · Daylight threshold
- Dusk to dawn function
- Off during the day, 10% output at night and 100% with Motion Sensor
- Detection range from 2m to 10m
- Selectable 3000K, 4000K or 5500K colour temperature
- · IP65 rated housing

Key Data

 Power
 16W

 Luminous Flux
 1600lm

 Colour Temperature
 4000K

 IP Rating
 IP65

Dimensions Ø325 x 110mm **Warranty** 3 Years

Compatible Accessories

Г	NET-51-04-59	Photocell Kit for Outdoor Lighting

NET LED Lighting

Buckingway Business Park, 300 Anderson Road, Swavesey, Cambridge, CB24 4UQ



Technical Specifications

Input Voltage (AC) 220-240V >0.9 **Power Factor Luminaire Efficacy** 100lm/W **LED Manufacturer** Jingrui **LED Type** SMD 2835 No. of LEDs **Driver Manufacturer** Merrytek **Driver Output Voltage (DC)** 36-42V Total Circuit Power (W) 16W **Electrical Class** 1 >80 CRI **Colour Rendering** 115° **Lamp Viewing Angle Dimmable** No

Operating Temp. 0°C to +45°C
Lifespan LM80 35,000 Hours
UGR Rating More than 19
Weight 1.13Kg

Manufacturer NET LED Lighting

Fire Rating V2 Luminous Flux Factor 5%

Self Test Selectable
Housing Colour White

Housing MaterialPolycarbonateBattery PackLi-on 3.7VDiffuser MaterialPolycarbonateEmergency Kit1 Year Warranty


Emergency Operation >3H

Emergency Pack Streamer

Sensor IP Rating IP20

Standby Dimming Level 0% / 10%

Corridor Function Yes



Other Options

	Description
NET-33-06-40	Duxford Bulkhead Multi-Wattage 4000K IP65 Standard
NET-33-06-42	Duxford Bulkhead Multi-Wattage 4000K IP65 Emergency/Self Test
NET-33-06-44	Duxford Bulkhead 4000K IP65 16W Microwave Sensor
NET-33-06-46	Duxford Bulkhead 4000K IP65 16W Microwave Sensor Emergency/Self Test

NET LED Lighting

Buckingway Business Park, 300 Anderson Road, Swavesey, Cambridge, CB24 4UQ



SHATTERPROOF POLYCARBONATE DIFFUSER

Prevents the fitting from breaking into multiple small pieces

IP65 RATED HOUSING

Protect your bulkhead from water and dust



4K



SELECTABLE COLOUR TEMPERATURE

Choose your colour temperature 3000K, 4000K or 5500K



MULTI WATTAGE DRIVER

Choose between 12W, 14W, 16W or 18W at the time of installation

NOT on Microwave Sensor options

NEW

MANUAL OR SELF TEST EMERGENCY SELECTABLE

Choose between manual emergency or self test emergency at the time of installation

Emergency options only

DUSK TO DAWN FUNCTION

Detects ambient light levels and adjusts the light accordingly

Photocell options only

PUSH CONNECTOR

Reduce installation time with easy-to-use push fit terminals



SUITABLE FOR BESA BOX INSTALLATION

Save time on site with pre-made cable entry points



Featuring a 0 or 10% Standby Mode, 2-10m detection range and 5sec to 10min hold time

Microwave Sensor options only

