

NEWTON METAL BULKHEAD MULTI-WATTAGE TRI-COLOUR IP65 MICROWAVE

NET-33-06-67



Features & Benefits

- Manual or self test emergency operation
- Integral Microwave Sensor
- 0% or 10% Standby Mode
- 2-10m detection range
- 5sec-10min hold time
- Selectable colour temperature 3000K, 4000K or 5500K

Key Data

| | |
|---------------------------|-------------------|
| Power | 16W |
| Luminous Flux | 1600lm |
| Colour Temperature | 3000K/4000K/5500K |
| IP Rating | IP65 |
| IK Rating | IK10 |
| Dimensions | Ø350 x 106mm |
| Warranty | 3 Years |

Compatible Accessories

| | |
|--------------|------------------------------------|
| NET-51-04-59 | Photocell Kit for Outdoor Lighting |
|--------------|------------------------------------|

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk



ORDER BY 6PM
FOR NEXT DAY DELIVERY

Technical Specifications

| | |
|----------------------------|------------------|
| Input Voltage (AC) | 220-240V |
| Power Factor | >0.9 |
| Luminaire Efficacy | 100lm/W |
| LED Manufacturer | Hongliitronic |
| LED Type | SMD 2835 |
| No. of LEDs | 52 |
| Driver Manufacturer | Merrytek |
| Driver Output Voltage (DC) | 36-42V |
| Total Circuit Power (W) | 16W |
| Electrical Class | 1 |
| Colour Rendering | >80 CRI |
| Lamp Viewing Angle | 115° |
| Dimmable | No |
| Operating Temp. | 0°C to +45°C |
| Lifespan LM80 | 35,000 Hours |
| UGR Rating | More than 19 |
| Weight | 3.4Kg |
| Manufacturer | NET LED Lighting |
| Fire Rating | V0 |
| Hours Maintained | 3 Hours |
| Luminous Flux Factor | 5% |
| Max. Detection Distance | 6m |
| Self Test | Selectable |
| Housing Colour | Black |
| Housing Material | Aluminium |
| Battery Pack | Li-on 3.7V |
| Diffuser Material | Polycarbonate |
| Emergency Kit | 1 Year Warranty |
| Emergency Operation | >3H |
| Emergency Pack | Streamer |
| Max. Detection Area | 6m |
| Sensor Manufacturer | Merrytek |
| Sensor IP Rating | IP20 |
| Standby Dimming Level | 0% / 10% |
| Corridor Function | Yes |

Other Options

| Description | |
|--------------|--|
| NET-33-06-61 | Newton Metal Bulkhead Multi-Wattage Tri-Colour IP65 Standard |
| NET-33-06-63 | Newton Metal Bulkhead Multi-Wattage Tri-Colour IP65 Emergency/Self Test |
| NET-33-06-65 | Newton Metal Bulkhead Multi-Wattage Tri-Colour IP65 Microwave Sensor |
| NET-33-06-67 | Newton Metal Bulkhead Multi-Wattage Tri-Colour IP65 Microwave Sensor Emergency/Self Test |
| NET-33-06-74 | Newton Metal Bulkhead Multi-Wattage Tri-Colour IP65 Photocell |
| NET-33-06-75 | Newton Metal Bulkhead Multi-Wattage Tri-Colour IP65 Photocell Emergency/Self Test |

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ



ORDER BY 6PM
FOR NEXT DAY DELIVERY

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk

3K

4K

5.5K

SHATTERPROOF POLYCARBONATE DIFFUSER

Designed to prevent the diffuser shattering into small, indistinct pieces

PUSH CONNECTOR

Reduce installation time with easy-to-use push fit terminals

DUSK TO DAWN FUNCTION

Detects ambient light levels and adjusts the light accordingly

Photocell options only

INTEGRAL MICROWAVE SENSOR

Featuring a 0 or 10% Standby Mode, 2-10m detection range and 5sec to 10min hold time

Microwave Sensor options only

SELECTABLE COLOUR TEMPERATURE

Choose your colour temperature 3000K, 4000K or 5500K

NEW

MANUAL OR SELF TEST EMERGENCY SELECTABLE

Choose between manual emergency or self test emergency at the time of installation

Emergency options only

NEW

IK10 AND IP65 ALUMINIUM HOUSING

Protect your fitting from harsh weather and impact

MULTI WATTAGE DRIVER

Choose between 12W, 14W, 16W or 18W at the time of installation

NOT on Microwave Sensor options

