


## NEWTON METAL BULKHEAD MULTI-WATTAGE TRI-COLOUR IP65 PHOTOCELL

NET-33-06-74



### Features & Benefits

- Dusk to dawn function
- Choose between 12W, 14W, 16W or 18W at the time of installation
- Selectable colour temperature 3000K, 4000K or 5500K
- Shatterproof polycarbonate diffuser
- Push connector for easy installation
- IP65 and IK10 rated housing

### Key Data

<b>Power</b>	12W/14W/16W/18W
<b>Luminous Flux</b>	1200lm/1400lm/1600lm/1800lm
<b>Colour Temperature</b>	3000K/4000K/5500K
<b>IP Rating</b>	IP65
<b>IK Rating</b>	IK10
<b>Dimensions</b>	Ø350 x 106mm
<b>Warranty</b>	3 Years

### NET LED Lighting

Buckingway Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ

T: 01223 851505 | [sales@netled.co.uk](mailto:sales@netled.co.uk) | [www.netled.co.uk](http://www.netled.co.uk)



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

## Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.9
Luminaire Efficacy	100lm/W
LED Manufacturer	Hongliitronic
LED Type	SMD 2835
No. of LEDs	52
Driver Manufacturer	Tridonic
Driver Output Voltage (DC)	36-42V
Total Circuit Power (W)	12W/14W/16W/18W
Electrical Class	1
Colour Rendering	>80 CRI
Lamp Viewing Angle	115°
Dimmable	No
Operating Temp.	-15°C to +45°C
Lifespan LM80	35,000 Hours
UGR Rating	More than 19
Weight	3.4Kg
Manufacturer	NET LED Lighting
Fire Rating	V0
Lux Levels	5lux - 400lux
Housing Colour	Black
Housing Material	Aluminium
Diffuser Material	Polycarbonate
Sensor IP Rating	IP20

## Other Options

Description	
NET-33-06-61	Newton Metal Bulkhead Multi-Wattage Tri-Colour IP65 Standard
NET-33-06-63	Newton Metal Bulkhead Multi-Wattage Tri-Colour IP65 Emergency/Self Test
NET-33-06-65	Newton Metal Bulkhead Multi-Wattage Tri-Colour IP65 Microwave Sensor
NET-33-06-67	Newton Metal Bulkhead Multi-Wattage Tri-Colour IP65 Microwave Sensor Emergency/Self Test
NET-33-06-74	Newton Metal Bulkhead Multi-Wattage Tri-Colour IP65 Photocell
NET-33-06-75	Newton Metal Bulkhead Multi-Wattage Tri-Colour IP65 Photocell Emergency/Self Test

### NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

T: 01223 851505 | [sales@netled.co.uk](mailto:sales@netled.co.uk) | [www.netled.co.uk](http://www.netled.co.uk)

3K

4K

5.5K

## SHATTERPROOF POLYCARBONATE DIFFUSER

Designed to prevent the diffuser shattering into small, indistinct pieces

## PUSH CONNECTOR

Reduce installation time with easy-to-use push fit terminals

## DUSK TO DAWN FUNCTION

Detects ambient light levels and adjusts the light accordingly

*Photocell options only*

## INTEGRAL MICROWAVE SENSOR

Featuring a 0 or 10% Standby Mode, 2-10m detection range and 5sec to 10min hold time

*Microwave Sensor options only*

## SELECTABLE COLOUR TEMPERATURE

Choose your colour temperature 3000K, 4000K or 5500K

**NEW**

## MANUAL OR SELF TEST EMERGENCY SELECTABLE

Choose between manual emergency or self test emergency at the time of installation

*Emergency options only*

**NEW**

## IK10 AND IP65 ALUMINIUM HOUSING

Protect your fitting from harsh weather and impact

## MULTI WATTAGE DRIVER

Choose between 12W, 14W, 16W or 18W at the time of installation

*NOT on Microwave Sensor options*

