


**NEWTON WHITE POLYCARBONATE BULKHEAD MULTI-WATTAGE 4000K IP65**

NET-33-06-80



**Features & Benefits**

- Choose between 12W, 14W, 16W or 18W at the time of installation
- Shatterproof polycarbonate diffuser
- Push connector for easy installation
- IP65 rated housing

**Key Data**

<b>Power</b>	12W/14W/16W/18W
<b>Luminous Flux</b>	1200lm/1400lm/1600lm/1800lm
<b>Colour Temperature</b>	4000K
<b>IP Rating</b>	IP65
<b>IK Rating</b>	IK10
<b>Dimensions</b>	Ø282 x 86.5mm
<b>Warranty</b>	3 Years

**Compatible Accessories**

NET-51-04-59	Photocell Kit for Outdoor Lighting
--------------	------------------------------------

**NET LED Lighting**

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ


T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

## Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.9
Luminaire Efficacy	100lm/W
LED Manufacturer	Hongliitronic
LED Type	SMD 2835
No. of LEDs	52
Driver Manufacturer	Tridonic
Driver Output Voltage (DC)	36-42V
Total Circuit Power (W)	12W/14W/16W/18W
Electrical Class	1
Colour Rendering	>80 CRI
Lamp Viewing Angle	115°
Dimmable	No
Operating Temp.	-15°C to +45°C
Lifespan LM80	35,000 Hours
UGR Rating	More than 19
Weight	1.04Kg
Manufacturer	NET LED Lighting
Fire Rating	V0
Housing Colour	White
Housing Material	Polycarbonate
Diffuser Material	Polycarbonate



## Other Options

Description	
NET-33-06-80	Newton White Polycarbonate Bulkhead Multi-Wattage 4000K IP65 Standard
NET-33-06-88	Newton White Polycarbonate Bulkhead Multi-Wattage 4000K IP65 Emergency/Self Test
NET-33-06-84	Newton White Polycarbonate Bulkhead 4000K IP65 16W Microwave Sensor
NET-33-06-86	Newton White Polycarbonate Bulkhead 4000K IP65 16W Microwave Sensor Emergency/Self Test

### NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk

3K

4K

5.5K

## INTEGRAL MICROWAVE SENSOR

Featuring a 0 or 10% Standby Mode, 2-10m detection range and 5sec to 10min hold time

*Microwave Sensor options only*

## SELECTABLE COLOUR TEMPERATURE

Choose your colour temperature 3000K, 4000K or 5500K

## SHATTERPROOF POLYCARBONATE DIFFUSER

Designed to prevent the diffuser shattering into small, indistinct pieces

**NEW**

## MANUAL OR SELF TEST EMERGENCY SELECTABLE

Choose between manual emergency or self test emergency at the time of installation

*Emergency options only*

## DUSK TO DAWN FUNCTION

Detects ambient light levels and adjusts the light accordingly

*Photocell options only*

## PUSH CONNECTOR

Reduce installation time with easy-to-use push fit terminals

## REAR OR SIDE CABLE ENTRY

Protect your wiring from harsh weather and possible tampering

## IP65 RATED HOUSING

Protect your bulkhead from water and dust