

KINGSTON PANEL UGR<19 TUNABLE WHITE 600X600 2700K-6500K 30W TP(A)

NET-39-03-31







Features & Benefits

- · Emergency function
- Tunable colour temperature 2700K-6500K
- Controllable via app or Dimmable/Scene Switch
- · Low glare diffuser with UGR rating <19
- TP(a) flammability-rated diffuser
- PMMA Light Guide path for even light distribution

Key Data

Power 30W Luminous Flux 3300lm

Colour Temperature Tunable 2700K-6500K
IP Rating IP40 Front/IP20 Rear
Dimensions 595 x 595 x 10mm

Warranty 5 Years (Registration Required)

Compatible Accessories

NET-39-16-01	Recess Clips (set of 4)
NET-46-16-02	Universal LED Panel Suspension Kit
NET-39-03-47	Panel Recessed Frame 600x600mm
NET-60-16-80	Tridonic Bluetooth Multifunction Dimmable/Scene Switch
NET-39-03-39	Panel Surface Box 600x600mm

NET LED Lighting

Buckingway Business Park, 300 Anderson Road, Swavesey, Cambridge, CB24 4UQ



Technical Specifications

Input Voltage (AC) 220-240V **Power Factor** >0.95 **Luminaire Efficacy** 122lm/W **LED Manufacturer** JUFEI **LED Type** SMD 4014 No. of LEDs 240 **Driver Manufacturer** Tridonic **Driver Output Voltage (DC)** 33-42V Total Circuit Power (W) 30W **Electrical Class** 3 >80 CRI **Colour Rendering** 95° **Lamp Viewing Angle Dimmable** Yes Flicker-Free Yes


Operating Temp. 0°C to +45°C Lifespan LM80 50,000 Hours

Diffuser Flammability Rating TP(a)
UGR Rating Less than 19
Diffuser/LGP Material PC/PMMA
Weight 2.9Kg
Manufacturer Lumlux Corp.

Frame Colour White
Hours Maintained 3H
Luminous Flux Factor 10%
Self Test No
Battery Pack LiFePO4

Dimming Input TypeBluetooth TunableEmergency Kit3 Year Warranty

Emergency Operation >3H



Other Options

	Description
NET-39-03-30	Kingston Panel UGR<19 Tunable White 600x600 2700K-6500K 30W TP(a) Standard
NET-39-03-31	Kingston Panel UGR<19 Tunable White 600x600 2700K-6500K 30W TP(a) Emergency
NET-39-03-59	Kingston Panel UGR<19 Tunable White 600x600 2700K-6500K 30W TP(a) Self Test Emergency

NET LED Lighting

Buckingway Business Park, 300 Anderson Road, Swavesey, Cambridge, CB24 4UQ



Control the colour temperature and brightness of your lighting directly from your phone or tablet.

Control multiple or individual fittings, or set the scene with pre-set colours and brightness levels.



2700K - 6500K

Don't forget to download the free App!

Using your phone's camera, scan the QR code to download the Tridonic 4remote BT App!







