

TRINITY SURFACE LINEAR TRI-COLOUR 1800MM (6FT) 41W/60W SELF TEST

NET-41-11-54



**Self Test
Emergency
operation**

Save time and money with a fitting that carries out its own testing in line with relevant standards

Tri-Colour

Choose your colour temperature (3000K, 4000K or 5700K) at the time of installation

Features & Benefits

- Self Test Emergency function
- Selectable power setting (41W or 60W) at the time of installation
- Choose your colour temperature at the time of installation (3000K, 4000K or 5700K)

Key Data

Power	41W/60W
Luminous Flux	5760lm/8625lm
Colour Temperature	3000K/4000K/5700K
IP Rating	IP20
Dimensions	1800 x 170 x 79mm
Warranty	5 Years (Registration Required)

Compatible Accessories

NET-51-11-02	Cambridge/Trinity Suspension Kit
--------------	----------------------------------

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ


T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk



ORDER BY 6PM
FOR NEXT DAY DELIVERY

Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.9
Luminaire Efficacy	143lm/W
LED Manufacturer	Jingrui
LED Type	SMD 2835
No. of LEDs	760
Driver Manufacturer	Tridonic
Driver Output Voltage (DC)	60V
Total Circuit Power (W)	41W/60W
Electrical Class	1
Colour Rendering	>80 CRI
Lamp Viewing Angle	120°
Dimmable	No
Flicker-Free	Yes
Operating Temp.	0°C to +40°C
Lifespan LM80	50,000 Hours
UGR Rating	More than 22
Weight	3.510Kg
Manufacturer	Senselite Optoelectronic Technology Co. Ltd
Fire Rating	V2
Luminous Flux Factor	9.75%/6.6%
Self Test	Yes
Housing Colour	White
Housing Material	Steel
Battery Pack	LiFePO4
Diffuser Material	Polycarbonate
Emergency Kit	3 Year Warranty
Emergency Operation	>3H
Emergency Pack	Streamer



Other Options

Description	
NET-41-11-50	Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Standard
NET-41-11-52	Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Emergency
NET-41-11-54	Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Self Test Emergency
NET-41-11-56	Trinity Surface Linear Tri-Colour 1800mm (6ft) 60W Dimmable one4all
NET-41-11-58	Trinity Surface Linear Tri-Colour 1800mm (6ft) 60W Dimmable Emergency
NET-41-11-51	Trinity Surface Linear Tri-Colour 1800mm (6ft) 60W Dimmable Self Test Emergency
NET-41-11-53	Trinity Surface Linear Tri-Colour 1800mm (6ft) 60W Dimmable DALI Emergency
NET-41-11-55	Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Microwave Sensor
NET-41-11-57	Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Microwave Sensor Emergency
NET-41-11-59	Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Microwave Sensor Self Test Emergency

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ



ORDER BY 6PM
FOR NEXT DAY DELIVERY

SELECTABLE COLOUR TEMPERATURE

Choose your colour temperature at the time of installation 3000K, 4000K or 5700K



DUAL WATTAGE TRIDONIC DRIVER

Choose the power setting at the time of installation

NEW

MANUAL OR SELF TEST EMERGENCY SELECTABLE

Choose between manual emergency or self test emergency at the time of installation

Emergency options only

INTEGRAL MICROWAVE SENSOR WITH 6M DETECTION DISTANCE AND 5S-30MIN HOLD TIME

Save energy costs with a fitting that only lights the room when movement is detected

Microwave Sensor options only

WIRELESS CONTROL

Control the panel remotely via smartphone or tablet with it's Bluetooth Dimmable Driver

Bluetooth options only

PUSH CONNECTOR

Reduce installation time with easy-to-use push fit terminals

REAR OR END CABLE ENTRY

Create seamless end-to-end lighting designs

