

TRINITY SURFACE LINEAR TRI-COLOUR 1800MM (6FT) 41W/60W MICROWAVE

NET-41-11-55



Features & Benefits

- Integral Microwave Sensor
- Selectable power setting (41W or 60W) at the time of installation
- Choose your colour temperature at the time of installation (3000K, 4000K or 5700K)

Key Data

| | |
|---------------------------|---------------------------------|
| Power | 41W/60W |
| Luminous Flux | 5760lm/8625lm |
| Colour Temperature | 3000K/4000K/5700K |
| IP Rating | IP20 |
| Dimensions | 1800 x 170 x 79mm |
| Warranty | 5 Years (Registration Required) |

Compatible Accessories

| | |
|--------------|----------------------------------|
| NET-51-11-02 | Cambridge/Trinity Suspension Kit |
|--------------|----------------------------------|

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ


T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk



ORDER BY 6PM
FOR NEXT DAY DELIVERY

Technical Specifications

| | |
|----------------------------|---------------------------------------------|
| Input Voltage (AC) | 220-240V |
| Power Factor | >0.9 |
| Luminaire Efficacy | 143lm/W |
| LED Manufacturer | Jingrui |
| LED Type | SMD 2835 |
| No. of LEDs | 760 |
| Driver Manufacturer | Tridonic |
| Driver Output Voltage (DC) | 60V |
| Total Circuit Power (W) | 41W/60W |
| Electrical Class | 1 |
| Colour Rendering | >80 CRI |
| Lamp Viewing Angle | 120° |
| Dimmable | No |
| Flicker-Free | Yes |
| Operating Temp. | 0°C to +40°C |
| Lifespan LM80 | 50,000 Hours |
| UGR Rating | More than 22 |
| Weight | 3.510Kg |
| Manufacturer | Senselite Optoelectronic Technology Co. Ltd |
| Fire Rating | V2 |
| Lux Levels | 2lux - 50lux or Disabled |
| Max. Detection Distance | 6m |
| Housing Colour | White |
| Housing Material | Steel |
| Detection Angle | 150°(wall mt) / 360°(ceiling mt) |
| Diffuser Material | Polycarbonate |
| Duration | 5s - 30min |
| Sensor Manufacturer | Merrytek |
| Sensor IP Rating | IP20 |



Other Options

| Description | |
|--------------|---------------------------------------------------------------------------------------------|
| NET-41-11-50 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Standard |
| NET-41-11-52 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Emergency |
| NET-41-11-54 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Self Test Emergency |
| NET-41-11-56 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 60W Dimmable one4all |
| NET-41-11-58 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 60W Dimmable Emergency |
| NET-41-11-51 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 60W Dimmable Self Test Emergency |
| NET-41-11-53 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 60W Dimmable DALI Emergency |
| NET-41-11-55 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Microwave Sensor |
| NET-41-11-57 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Microwave Sensor Emergency |
| NET-41-11-59 | Trinity Surface Linear Tri-Colour 1800mm (6ft) 41W/60W Microwave Sensor Self Test Emergency |

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ



ORDER BY 6PM
FOR NEXT DAY DELIVERY

SELECTABLE COLOUR TEMPERATURE

Choose your colour temperature at the time of installation 3000K, 4000K or 5700K



DUAL WATTAGE TRIDONIC DRIVER

Choose the power setting at the time of installation

NEW

MANUAL OR SELF TEST EMERGENCY SELECTABLE

Choose between manual emergency or self test emergency at the time of installation

Emergency options only

INTEGRAL MICROWAVE SENSOR WITH 6M DETECTION DISTANCE AND 5S-30MIN HOLD TIME

Save energy costs with a fitting that only lights the room when movement is detected

Microwave Sensor options only

WIRELESS CONTROL

Control the panel remotely via smartphone or tablet with it's Bluetooth Dimmable Driver

Bluetooth options only

PUSH CONNECTOR

Reduce installation time with easy-to-use push fit terminals

REAR OR END CABLE ENTRY

Create seamless end-to-end lighting designs

