

CAXTON DOWNLIGHT TRI-COLOUR 3" 5W TP(A) EMERGENCY/SELF TEST


NET-49-05-71


**3 Hour
Emergency
operation**

The integral Emergency Battery ensures the fitting stays on in the event of an emergency or power failure - can be Self Test Emergency or standard 3H Emergency


Tri-Colour

Choose your colour temperature (3000K, 4000K or 5500K) at the time of installation


Features & Benefits

- 3H Emergency function
- Ø90-100mm cut out size
- TP(a) flammability-rated diffuser
- Selectable 3000K, 4000K or 5500K colour temperature
- Shatterproof polycarbonate diffuser
- Stainless steel retaining clips

Key Data

Power	5W
Luminous Flux	475lm/500lm/470lm
Colour Temperature	3000K/4000K/5500K
IP Rating	IP65 Front/IP20 Rear
Dimensions	Ø110 x 45mm
Warranty	5 Years (Registration Required)

Compatible Accessories

NET-61-35-13	Buckden Self Test Emergency Kit 3W for Panels and Downlights
NET-42-43-05	Merrytek Ceiling Mount Microwave Sensor

NET LED Lighting


 Buckingham Business Park, 300 Anderson Road,
 Swavesey, Cambridge, CB24 4UQ

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk


ORDER BY 6PM
 FOR NEXT DAY DELIVERY

Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	>0.5
Luminaire Efficacy	95lm/W
LED Manufacturer	Hongliitronic
LED Type	SMD 2835
No. of LEDs	48
Driver Manufacturer	Tridonic Essence Series
Driver Output Voltage (DC)	29-42V
Total Circuit Power (W)	5W
Electrical Class	3
Colour Rendering	>80 CRI
Lamp Viewing Angle	100°
Dimmable	No
Flicker-Free	Yes
Operating Temp.	0°C to +45°C
Lifespan LM80	50,000 Hours
Diffuser Flammability Rating	TP(a)
UGR Rating	More than 19
Weight	0.29Kg
Manufacturer	CREP Optoelectronics
Hours Maintained	3H
Luminous Flux Factor	60%
Self Test	No
Cut-Out Size	ø90-100mm
Housing Colour	White
Housing Material	Aluminium
Battery Pack	LiFePO4 3.2V 4.5Ah
Emergency Kit	3 Year Warranty
Emergency Operation	>3H
Emergency Pack	Streamer



Other Options

Description	
NET-49-05-70	Caxton Downlight Tri-Colour 3" 5W TP(a) Standard
NET-49-05-71	Caxton Downlight Tri-Colour 3" 5W TP(a) Emergency/Self Test

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ



ORDER BY 6PM
FOR NEXT DAY DELIVERY

Ø90-210MM CUT-OUT SIZES

Available in 3", 4", 6" and 8",
these downlights are designed
to fit most existing holes

STAINLESS STEEL RETAINING CLIPS


Quick and simple installation
with no need for additional
tools



TRIDONIC DIMMABLE DRIVER

Customise lighting levels and
reduce electricity consumption

Dimmable options only




TP(A) FLAMMABILITY RATED DIFFUSER

Comply with Building Regulations
and prevent flaming particles



IP65 RATED FASCIA

Protect the downlight
from water and dust



SHATTERPROOF POLYCARBONATE DIFFUSER

Designed to prevent
the diffuser shattering into
small, indistinct pieces



SELECTABLE COLOUR TEMPERATURE

Choose your colour
temperature 3000K,
4000K or 5500K

3K

4K

5.5K

NEW

MANUAL OR SELF TEST EMERGENCY SELECTABLE

Choose between manual
emergency or self test
emergency at the time
of installation

Emergency options only

