


CAMBRIDGE SURFACE LINEAR UGR<19 TRI-COLOUR 1500MM (5FT) 50W DIMMABLE

NET-51-11-82



**Features & Benefits**

- Tridonic one4all Dimming - DALI 1 & 2 and switchDIM (Push)
- Low glare UGR<19 prismatic diffuser
- Selectable 3000K, 4000K or 5700K colour temperature
- Rear or end cable entry
- Hinged diffuser for quick and easy access to wiring
- Push connector for easy installation

**Key Data**

<b>Power</b>	50W
<b>Luminous Flux</b>	6100lm
<b>Colour Temperature</b>	3000K/4000K/5700K
<b>IP Rating</b>	IP20
<b>Dimensions</b>	1500 x 207 x 71mm
<b>Warranty</b>	5 Years (Registration Required)

**Compatible Accessories**

NET-51-11-02	Cambridge/Trinity Suspension Kit
--------------	----------------------------------

**NET LED Lighting**

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

## Technical Specifications

Input Voltage (AC)	220-240V
Power Factor	0.9
Luminaire Efficacy	128lm/W
LED Type	SMD 2835
Driver Manufacturer	Tridonic
Driver Output Voltage (DC)	87-93V
Total Circuit Power (W)	50W
Electrical Class	1
Colour Rendering	80 CRI
Lamp Viewing Angle	80°
Dimmable	Yes
Flicker-Free	Yes
Operating Temp.	0°C to +40°C
Lifespan LM80	50,000 Hours
UGR Rating	Less than 19
Weight	3.5Kg
Manufacturer	Sealite Co. Ltd.
Fire Rating	V2
Housing Colour	White
Housing Material	Steel
Diffuser Material	Polycarbonate
Dimming Input Type	one4all Dimming - DALI 1 & 2 and switchDIM (Push)

## Other Options

Description	
NET-51-11-61	Cambridge Surface Linear UGR<19 Tri-Colour 1500mm (5ft) 40W/50W Standard
NET-51-11-81	Cambridge Surface Linear UGR<19 Tri-Colour 1500mm (5ft) 40W/50W Emergency/Self Test
NET-51-11-82	Cambridge Surface Linear UGR<19 Tri-Colour 1500mm (5ft) 50W Dimmable one4all
NET-51-11-83	Cambridge Surface Linear UGR<19 Tri-Colour 1500mm (5ft) 50W Dimmable Emergency/Self Test
NET-51-11-84	Cambridge Surface Linear UGR<19 Tri-Colour 1500mm (5ft) 50W Dimmable DALI Emergency
NET-51-11-85	Cambridge Surface Linear UGR<19 Tri-Colour 1500mm (5ft) 50W Microwave Sensor
NET-51-11-86	Cambridge Surface Linear UGR<19 Tri-Colour 1500mm (5ft) 50W Microwave Sensor Emergency/Self Test

### NET LED Lighting

Buckingham Business Park, 300 Anderson Road,  
Swavesey, Cambridge, CB24 4UQ



**ORDER BY 6PM**  
FOR NEXT DAY DELIVERY

T: 01223 851505 | [sales@netled.co.uk](mailto:sales@netled.co.uk) | [www.netled.co.uk](http://www.netled.co.uk)