

#### ASHLEY SLIM DOWNLIGHT 4000K 6" 15W STANDARD

NET-53-05-83







#### **Features & Benefits**

- Ø175mm cut out size
- Slim, low profile design
- Stainless steel retaining clips
- Single colour temperature 4000K
- 10mm depth

#### **Key Data**

Power15WLuminous Flux1350ImColour Temperature4000KIP RatingIP20

DimensionsØ190 x 10mmWarranty3 Years

#### **Compatible Accessories**

NET-50-12-08	Manual/Self Test Emergency Selectable LED Converter 2.5W
NET-61-33-03	DALI Emergency Kit 3W
NET-61-35-13	Buckden Self Test Emergency Kit 3W for Panels and Downlights
NET-42-43-05	Merrytek Ceiling Mount Microwave Sensor

#### **NET LED Lighting**

Buckingway Business Park, 300 Anderson Road, Swavesey, Cambridge, CB24 4UQ



## **Technical Specifications**

Input Voltage (AC)220-240VPower Factor>0.5Luminaire Efficacy90lm/WLED ManufacturerMTCLED TypeSMD 2835

No. of LEDs 89

**Driver Manufacturer** Hooger Electronics

Driver Output Voltage (DC)

22-42V

Total Circuit Power (W)

Electrical Class

Colour Rendering

Lamp Viewing Angle

Dimmable

No

Flicker-Free


Yes

Operating Temp. 0°C to +35°C
Lifespan LM80 35,000 Hours

UGR Rating 27
Weight 0.40Kg

Manufacturer Kingsway Lighting

Cut-Out SizeØ175mmHousing ColourWhiteHousing MaterialAluminium



All units are in mm

### Other Options

	Description
NET-53-05-83	Ashley Slim Downlight 4000K 6" 15W Standard
NET-53-05-91	Ashley Slim Downlight 4000K 6" 15W Emergency/Self Test

#### **NET LED Lighting**

Buckingway Business Park, 300 Anderson Road, Swavesey, Cambridge, CB24 4UQ



# 10MM DEPTH Essential for shallow ceiling voids **STAINLESS** STEEL RETAINING CLIPS Quick and simple installation with no need for additional tools Ø135-210MM **CUT-OUT SIZE** Retrofit over an existing 4K cut-out from anywhere between

Ø135mm and Ø210mm

Create a focused environment perfect for offices and commercial spaces

4000K COLOUR TEMPERATURE