

ASHLEY SLIM DOWNLIGHT 4000K 8" 18W STANDARD

NET-53-05-85







Features & Benefits

- Ø210mm cut out size
- Slim, low profile design
- · Stainless steel retaining clips
- Single colour temperature 4000K
- 10mm depth

Key Data

Power18WLuminous Flux1750ImColour Temperature4000KIP RatingIP20

DimensionsØ225 x 10mmWarranty3 Years

Compatible Accessories

NET-50-12-08	Manual/Self Test Emergency Selectable LED Converter 2.5W
NET-61-33-03	DALI Emergency Kit 3W
NET-61-35-13	Buckden Self Test Emergency Kit 3W for Panels and Downlights
NET-42-43-05	Merrytek Ceiling Mount Microwave Sensor

NET LED Lighting

Buckingway Business Park, 300 Anderson Road, Swavesey, Cambridge, CB24 4UQ



Technical Specifications

Input Voltage (AC) 220-240V

Power Factor >0.5

Luminaire Efficacy 97Im/W

LED Manufacturer MTC

LED Type SMD 2835

No. of LEDs 110

Driver Manufacturer Hooger Electronics

Driver Output Voltage (DC)

Total Circuit Power (W)

Electrical Class

Colour Rendering

Lamp Viewing Angle

Dimmable

No

Flicker-Free


Yes

Operating Temp. 0°C to +35°C Lifespan LM80 35,000 Hours

UGR Rating 27
Weight 0.42Kg

Manufacturer Kingsway Lighting

Cut-Out SizeØ210mmHousing ColourWhiteHousing MaterialAluminium



All units are in mm

Other Options

ĺ		Description
	NET-53-05-85	Ashley Slim Downlight 4000K 8" 18W Standard
	NET-53-05-92	Ashley Slim Downlight 4000K 8" 18W Emergency/Self Test

NET LED Lighting

Buckingway Business Park, 300 Anderson Road, Swavesey, Cambridge, CB24 4UQ



10MM DEPTH Essential for shallow ceiling voids **STAINLESS** STEEL RETAINING CLIPS Quick and simple installation with no need for additional tools Ø135-210MM **CUT-OUT SIZE** Retrofit over an existing 4K cut-out from anywhere between

Ø135mm and Ø210mm

Create a focused environment perfect for offices and commercial spaces

4000K COLOUR TEMPERATURE