

ASHLEY SLIM DOWNLIGHT 4000K 4" 10W EMERGENCY/SELF TEST

NET-53-05-90







Features & Benefits

- 3H Emergency function
- Ø135mm cut out size
- · Slim, low profile design
- Stainless steel retaining clips
- Single colour temperature 4000K
- 10mm depth

Key Data

Power 10W
Luminous Flux 900Im
Colour Temperature 4000K
IP Rating IP20

Dimensions Ø145 x 10mm **Warranty** 3 Years

Compatible Accessories

NET-42-43-26	Merrytek Dimming Driver up to 10W
NET-42-43-05	Merrytek Ceiling Mount Microwave Sensor

NET LED Lighting

Buckingway Business Park, 300 Anderson Road, Swavesey, Cambridge, CB24 4UQ



Technical Specifications

Input Voltage (AC)220-240VPower Factor>0.5Luminaire Efficacy90lm/WLED ManufacturerMTCLED TypeSMD 2835

No. of LEDs 60

Driver Manufacturer Hooger Electronics

Driver Output Voltage (DC)

22-42V

Total Circuit Power (W)

Electrical Class

2

Colour Rendering

>80 CRI

Lamp Viewing Angle

120°

Dimmable Optional Upgrade

Flicker-Free Yes

Operating Temp. 0°C to +35°C Lifespan LM80 35,000 Hours

 UGR Rating
 27

 Weight
 0.29Kg

Manufacturer Kingsway Lighting

Hours Maintained 3H

Luminous Flux Factor 30%

Self Test No

Cut-Out Size Ø135mm


Housing Colour White

Housing Material Aluminium

Battery Pack LiFePO4 3.2V 4.5A

Battery Pack LiFePO4 3.2V 4.5Ah
Emergency Kit 3 Year Warranty

Emergency Operation >3H
Emergency Pack Streamer



All units are in mm

Other Options

	Description
NET-53-05-81	Ashley Slim Downlight 4000K 4" 10W Standard
NET-53-05-90	Ashley Slim Downlight 4000K 4" 10W Emergency/Self Test

NET LED Lighting

Buckingway Business Park, 300 Anderson Road, Swavesey, Cambridge, CB24 4UQ



10MM DEPTH Essential for shallow ceiling voids **STAINLESS** STEEL RETAINING CLIPS Quick and simple installation with no need for additional tools Ø135-210MM **CUT-OUT SIZE** Retrofit over an existing 4K cut-out from anywhere between

Ø135mm and Ø210mm

Create a focused environment perfect for offices and commercial spaces

4000K COLOUR TEMPERATURE