


CARLTON T5 TUBE 5500K (2FT) 8W

NET-55-01-05



Features & Benefits

- Rotatable end caps
- Single colour temperature 5500K

Key Data

Power	8W
Luminous Flux	1120lm
Colour Temperature	5500K
IP Rating	IP20
Dimensions	563.2 x 22mm
Warranty	5 Years (Registration Required)

Compatible Accessories

NET-61-33-01	Foxlux Self Test Emergency Kit 5W
NET-50-12-10	Manual/Self Test Emergency Selectable LED Converter 2.5W
NET-50-33-01	Streamer 3H Emergency Kit 4.5W
NET-19-33-17	Liteplan DALI Emergency Kit 5W
NET-55-16-02	LED Tube Replacement Starter

NET LED Lighting

Buckingway Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ

T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk




ORDER BY 6PM
FOR NEXT DAY DELIVERY

Technical Specifications

Input Voltage (AC)	85-265V
Power Factor	>0.95
Luminaire Efficacy	130lm/W
LED Manufacturer	Sanan
LED Type	SMD 2835
Driver Manufacturer	Wiscoon Tech Co. Ltd
Driver Output Voltage (DC)	50-80V
Total Circuit Power (w)	8W
Electrical Class	2
Colour Rendering	>80 CRI
Lamp Viewing Angle	120°
Dimmable	No
Operating Temp.	-15°C to +45°C
Lifespan LM80	50,000 Hours
UGR Rating	22
Weight	0.16Kg
Manufacturer	Wiscoon Tech Co. Ltd.
Fire Rating	V2
Luminous Flux Factor	50%
Housing Colour	White
Housing Material	Aluminium
Diffuser Material	Polycarbonate

PRODUCT DIMENSIONS



All dimensions are in mm	A	B	C
NET-55-01-03	288	295	302
NET-55-01-05	549	556	563
NET-55-01-07	849	856	863
NET-55-01-08	849	856	863
NET-55-01-09	1149	1156	1163
NET-55-01-11	1449	1456	1463
NET-55-01-10	1149	1156	1163
NET-55-01-12	1449	1456	1463

Other Options

Description	
NET-55-01-03	Carlton T5 Tube 5500K (1ft) 4W
NET-55-01-05	Carlton T5 Tube 5500K (2ft) 8W
NET-55-01-07	Carlton T5 Tube 5500K (3ft) 9W
NET-55-01-09	Carlton T5 Tube 5500K (4ft) 11W
NET-55-01-11	Carlton T5 Tube 5500K (5ft) 14W
NET-55-01-10	Carlton T5 Tube 4000K (4ft) 11W
NET-55-01-12	Carlton T5 Tube 4000K (5ft) 14W
NET-55-01-08	Carlton T5 Tube 4000K (3ft) 9W

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ



ORDER BY 6PM
FOR NEXT DAY DELIVERY

4K

5.5K

**4000K AND
5500K COLOUR
TEMPERATURES
AVAILABLE**

Can be used for a variety of applications from commercial and retail spaces to residential environments

4K

5.5K

**4000K AND
5500K COLOUR
TEMPERATURES
AVAILABLE**

Can be used for a variety of applications from commercial and retail spaces to residential environments

T8



**DALI DIMMABLE
DRIVER
OPTIONS
AVAILABLE**

Customise lighting levels and reduce electricity consumption

DALI options only



**ROTATABLE
END CAPS**

Direct the light exactly where it's needed